

UNDERLAYS

Hurford's underlays are designed to be installed under our engineered hardwood flooring products. Both the HUSHwalk and EVERwalk are closed-cell underlays, which prevents the flattening out, seen in some open-cell foams. Retaining the shape prevents flooring movement and damage to clip lock joints, making for more effective sound control.



HUSHwalk Underlay (Premium)

Description: 2.0mm high density IXPE foam with 0.04mm PE film

Main raw material: High density cross-linked foam

Thickness: 2.0mm

Width: 1.1mtrs

Length: 22.8mtrs

Roll Size: 25m²/roll

Colour: Green

Density: 66kg/m³

STC Rating: 69dB

IIC Rating: 72dB

Benefits:

- HUSHWALK is our premium product, denser and quieter under foot
- Strong enough for the most demanding commercial installations
- High density cross-linked foam
- Moisture barrier attached – The PE film and IXPE (Irradiation cross linked polyolefin foam) act together as a moisture barrier
- Has a slightly thinner film, due to the much higher density of the IXPE foam layer
- Helps to eliminate sub-floor imperfections
- Suitable for use over both concrete and wood subfloors
- Lay flat polymers for easy installation
- Double sided tape for joining
- Superior thermal stability
- Mould and mildew resistant as well as non-allergenic
- Environmentally friendly, without CFC or HCFC's



EVERwalk Underlay (Standard)

Description: 2.0mm IXPE foam with 0.06mm PE film

Main raw material: Cross-linked foam

Thickness: 2.0mm

Width: 1.1mtrs

Length: 22.8mtrs

Roll Size: 25m²/roll

Colour: White

Density: 33kg/m³

STC Rating: 66dB

IIC Rating: 71dB

Benefits:

- EVERWALK is our standard underlay, with a medium density IXPE foam layer
- Quality underlay ideal for residential single story dwellings
- Cross-linked foam
- Moisture barrier attached – The PE film and IXPE (Irradiation cross linked polyolefin foam) act together as a moisture barrier
- Lay flat polymers for easy installation
- Suitable for use over both concrete and wood subfloors
- Helps to eliminate sub-floor imperfections
- Double sided tape for joining
- Superior thermal stability
- Mould and mildew resistant as well as non-allergenic
- Environmentally friendly, without CFC or HCFC's

Hurford Wholesale Pty Ltd

www.hurfords.com.au

QLD: (07) 3442 6300

NSW & ACT: (02) 4646 1406

VIC & TAS: (03) 8794 3300

SA & NT: (08) 8376 6694

WA: 0448 132 955

STC Rating = Sound Transmission Classification **IIC Rating** = Impact Insulation Class