# STRUCTApanel H2 12mm Timber Flooring Underlay





Introducing a brand new panel concept to the market - STRUCTApanel H2mm Timber Flooring Underlay. Made with durable materials and 5.5mm High Performance Hardboard Underlay. STRUCTApanel H2 12mm is a 12mm thick high performance panel primarily designed for flooring underlay where it provides a high performance, consistent, flat and durable alternative to other products in the market, with superior nail and staple holding capability.

# **FEATURES & BENEFITS**

- Australian made from sustainable certified plantation forestry
- Highly durable with resin/wax enriched surfaces
- High fixing capacity
- H2 Treated for termite resistance
- Double-sided
- Consistently flat with no internal delamination
- Easy to cut leaving smooth, clean edges
- Excellent adhesion to the sanded surface

### **APPLICATIONS**

Used as an underlay for timber strip flooring on top of the concrete

### **SHEET SIZES**

Sold as 2400x1200mm (actual size approx. 2420x1215mm)

## **TECHNICAL DATA**

- Typical minimum results when measured by a nata accredited third party testing facility
- Exceeds AS1859.1 High performance particleboard requirement
- Formaldehyde Emission E1

# **PERFORMANCE CRITERIA**

	STRUCTApanel	Plywood
Criteria	H2 12mm	12mm
Density - kg/m3	707	458.73
Thickness Swell - %	3.04	4.25
MOR - MPa	25.56	24.44
MOE - MPa	3342	1556
Surface water absorption - g/m2	26.2	534.46
Nail Holding - N	560	502
Surface Hardness – N	4550	3665

Distributed by:







